

Pneumatic Knocker		Designs and Sizes			singold		
Typ	Sizes	Designs:	Operating Temperature		Material		
			from	to	Lid and Ground plate	Tube	Striker Bolt
Kxxx	40	Standard Design	0	60	Aluminum	Steel-outside powder-coated	Steel zinc coated
Kxxx-N2	63	Special Model	0	80	Aluminum	Steel-outside powder-coated	Steel zinc coated
Kxxx-N3	80	Special Model	0	120	Aluminium	Steel-outside powder-coated	Steel zinc coated
Kxxx-S1	100	Special Model	0	60	Steel zinc coated	Steel-outside powder-coated	Steel zinc coated
Kxxx-S4	125	Special Model	0	140	Steel zinc coated	Steel-outside powder-coated	Steel zinc coated
Kxxx-T1	160	Special Model	0	60	Stainless Steel 1.4541	Steel-outside powder-coated	Steel zinc coated
Kxxx-T4		Special Model	0	140	Stainless Steel 1.4541	Steel-outside powder-coated	Steel zinc coated
Kxxx-V1		Special Model	0	60	Steel zinc coated	Steel-outside powder-coated	Vulkollan
Kxxx-K1		Special Model	0	60	Stainless Steel 1.4541	Stainless Steel 1.4301	Stainless steel 1.4021
Kxxx-K1PU		Special Model	0	60	Stainless Steel 1.4541	Stainless Steel 1.4301	Vulkollan
Kxxx-K4		Special Model	0	140	Stainless Steel 1.4541	Stainless Steel 1.4301	Stainless steel 1.4021



singold gerätetechnik gmbh DE 86830 Schwabmünchen

Telefon: +49 8232 / 710 36
 Telefax: +49 8232 / 710 39
 E-Mail: info@singold-tech.de
 Internet: www.singold-tech.de